Auri-D4 and Auri-D16 Docking Station

The docking stations allow for easy charging and management of Auri[™] receivers and are available in 4 or 16 unit options, with accessories such as the docking station case and intelligent cable management unit for the Auri-D16.

Contents

1x Auri-D4 or Auri-D16 Docking Station 1x LA-210 Power Supply 1x Quick Start Guide and Safety Data Sheet





Product Specifications

| Network | | | | | |
|-------------------------|----------------------------------------------------------------------------------------------------------------|--|--|--|--|
| Port speed | 100 Mbit | | | | |
| IP address | DHCP, static or link-local | | | | |
| Protocols | mDNS, UDP (unicast), RTP (multicast), RTCP (multicast) | | | | |
| Security | UDP communication AES256-GCM | | | | |
| Controls and Indication | | | | | |
| Buttons | Copy and Status buttons Recessed restart and factory reset buttons | | | | |
| Setup/Programming | Via Auri™ Manager Software over network | | | | |
| LEDs | Copy LED (red) and Status LED (amber), see handbook for states | | | | |
| Power | | | | | |
| Power Supply Input | 100-240 VAC, 50-60 Hz | | | | |
| Power Supply Output | 12 VDC, 4.0 A, 48 W | | | | |
| Power Supply Connector | 5.5 mm (.22 in.) OD x 2.3 mm (.09 in.) ID, barrel type | | | | |
| Power Cable | 1.8 m (72 in.) Input Power Cable, 1.1 m (43 in.) Output Cable | | | | |
| Physical | | | | | |
| Dimensions | Auri-D4 – 50 x 192 x 150 mm (1.97 x 7.56 x 5.89 in.) Auri-D16 – 50 x 192 x 375 mm (1.97 x 7.56 x 14.77 in.) | | | | |
| Unit Capacity | 4 or 16 Units | | | | |
| Weight | Auri-D4 – 0.65 kg (1.43 lbs.) Auri-D16 – 1.73 kg (3.81 lbs.) | | | | |
| Shipping Weight | Auri-D4 – 1.56 kg (3.44 lbs.) Auri-D16 – 2.79 kg (6.15 lbs.) | | | | |
| Colour | Black with chrome buttons | | | | |
| Mounting | Place on flat surface or use wall mounting slots | | | | |

www.auriaudio.com

| Environmental | | | |
|-----------------------------------------------------|--------------------------------------------|--|--|
| Temperature - Storage | -40 °C (-40 °F) to 70 °C (+158 °F) | | |
| Temperature - Operation | -10 °C (14 °F) to 40 °C (+104 °F) | | |
| Relative Humidity | 0 to 95% relative humidity, non-condensing | | |
| IP Rating | IP20 | | |
| Compliance | | | |
| itandards CE, UKCA, RCM, REACH, WEEE | | | |
| | | | |
| Specifications are subject to change without notice | | | |
| | | | |

Network Requirements

| Usage | Туре | Address | Port |
|------------------|------------------|-------------------------------------------|--------------|
| Device discovery | mDNS (Multicast) | 224.0.0.251 | 5353 |
| Control | UDP (Unicast) | Device IP (DHCP, Static or Link Local) | 55666, 56666 |
| Firmware Update | TFTP | Device IP | 69 |



AMPETRONIC Unit 2, Trentside Buisness Village, Farndon Road, Newark NG24 4XB, United Kingdom | Phone: +44.1636.610062 www.ampetronic.com LISTEN TECHNOLOGIES 14912 Heritage Crest Way, Bluffdale, Utah 84065-4818 USA | Phone: +1.801.233.8992 Toll-Free: 1.800.330.0891 www.listentech.com

The Bluetooth ® word marks and logos are registered trademarks owned by Bluetooth SIG,Inc. and any use of such marks by Listen Technologies and Ampetronic are under license. Other trademarks are trade names of their respective owners. Windows ® is a trademark of the Microsoft ® group of companies. 20240910 | UP3B602-1